

C3-415 - 8M/4K (was C3_4K)

Sensor specifications

Pixels	3840H x 2160V
Sensor size	5.568 x 3.132 mm
Shutter	Electronic Rolling Shutter
Sensor pixel size	1.45µm x 1.45µm
Frame rates	<ul style="list-style-type: none">• MJPG - 30fps in all modes• YUV 4:2:2 (YUYV)
Output frame sizes	3840×2160, 2592×1944, 2048×1563, 1920×1080, 1600×1200, 1280×720, 1280×960, 800×600, 640×480, 320×240, custom available on request
Manual control	<ul style="list-style-type: none">• Exposure• White balance (2000°K - 10000°K)• Gain• Gamma• Backlight compensation• Zoom, Pan, Tilt, Rotation• Low light compensation <hr/> <ul style="list-style-type: none">• Sharpness• Contrast• Saturation• Hue• Brightness• Anti-flicker frequency
Rated power	<ul style="list-style-type: none">• 2W max• 290mA @ 5V - MJPEG / YUYV
Supported OS	<ul style="list-style-type: none">• Windows• OSX• Linux• Android
Sensor	Sony IMX415

Variants

SKU	Filter	Chroma	Note
C3-415C-M12	9.5mm for wide angle lenses	RGB Color	M12 Most common use for wide angle and fish-eye lenses.
C3-415C-M12L	14.7mm for regular and telephoto lenses	RGB Color	M12L Modification for lenses above 6mm (typical)
C3-415C	Visible band-pass (IR CUT filter) LP0689_P1010	RGB Color	CS Essential for real-life colors
C3-415C-NF	No Filter	RGB Color	CS Full spectrum false color imaging
C3-415C-NIR1	Long-pass NIR 850nm filter LP0689-P1012	RGB Color	CS Blocks visible light, can see only Infrared.

Revision #8

Created 25 May 2025 16:28:29 by Saulius

Updated 25 May 2025 16:58:20 by Saulius