


Cables


Cables used with Kurokesu products specifications and reference

- Cable USB MICRO 1.5m with LOCK screws
- Cable USB MINI 1.5m with LOCK screws
- Cable USB USB-C 1.5m with LOCK screws
- Cable USB for C1 MICRO 1.5m

Cable USB MICRO 1.5m with LOCK screws



SKU	USB_CABLE_MICRO_1.5_LOCK
Length	1.5m
Plug A	USB Type A
Plug B	USB Type Micro B
Screw	M2
Screw spacing	13mm
Shell	PVC 45P BLACK
Wires	<ul style="list-style-type: none">• 24AWG*2C• 28AWG*1P
Outside diameter	4.5mm




Potted cable cross-section



Cable USB MINI 1.5m with LOCK screws



SKU	USB_CABLE_MINI_1.5_LOCK
Length	1.5m
Plug A	USB Type A
Plug B	USB Type Mini B
Screw	M2
Screw spacing	13mm
Shell	PVC 45P BLACK
Wires	<ul style="list-style-type: none">• 28AWG*1P• 24AWG*2C• ADB
Outside diameter	4.5mm (+/- 0.1mm)



Potted cable cross-section




Cable USB USB-C 1.5m with LOCK screws



SKU	CABLE_USB_USBC_1.5M_LOCK
Length	1.5m
Plug A	USB Type A
Plug B	USB Type C
Screw	M2
Screw spacing	15mm
Shell	PVC 45P BLACK
Wires	<ul style="list-style-type: none">• (32AWG*1P + EAM) * 2• 32AWG*1P• 24AWG*2C• EAB

Outside diameter	4.2mm (+/- 0.1mm)
------------------	-------------------



Potted cable cross-section




Cable USB for C1 MICRO

1.5m



SKU	CABLE_USB_1MM
Length	1.5m
Plug A	USB Type A
Plug B	1.00 mm Female Terminal
Receptacle	Wurth Electronics 665305124022
Shell	PVC 45P BLACK
Wires	<ul style="list-style-type: none">• 28AWG (7/0.12TS)• 0.75*5C• AL
Outside diameter	3.0mm (+/- 0.1mm)



Signal	Pin nr	Color
VCC	1	Red
D-	2	White
D+	3	Green
GND	4	Black
Shield	5	Brown

Potted cable cross-section

